

OPTISCREEN™

HIGH PERFORMANCE SCREENS

 HS-Harps

 HP-Harps

 HSP-Harps

OPTISCREEN™ HS, HP and HSP harps offer:

- low risk of clogging
- self-cleaning effect
- high screening capacity
- precise grain separation

They are suitable for:

- moist, sticky screenings
- reducing blockages on the screen
- longitudinal and transverse tensioners
- stationary systems
- mobile systems



Prellerstraße 5 • 44141 Dortmund • Germany

Phone +49 (0) 231-927398-0
Fax +49 (0) 231-927398-20

e-mail info@curt-ebert-siebtechnik.de
Internet www.curt-ebert-siebtechnik.de



OPTISCREEN™

HIGH PERFORMANCE SCREENS

Screen type

HS

HS-HARPS are screening media made of single, continuous in the sieve plane corrugated longitudinal wires, with square sieve openings in a diagonal hole arrangement.

OPTISCREEN™ HS HARPS are suitable for all screening machines. With cross connections and tensioning hooks for longitudinal and transverse tensioning machines.

Mesh sizes:
3 mm - 25,4 mm

Precision:



Performance:



Screen type

HP

HP-HARPS are screening media made of straight, longitudinal wires with fused-in PUR connections.

The clear width between the longitudinal wires is the mesh size.

OPTISCREEN™ HP HARPS are suitable for all longitudinally tensioned screening machines.

Mesh sizes:
3 mm - 25,4 mm

Precision:



Performance:



Screen type

HSP

HSP-HARPS consist of alternating straight and in the sieve plane horizontally corrugated wires lying next to each other. Both are held in place by fused in PUR cross-connections. This means that only the corrugated longitudinal wires have freedom of movement.

OPTISCREEN™ HSP HARPS are suitable for all screening machines. With cross connections and tensioning hooks for longitudinal and transverse tensioning machines.

Mesh sizes:
3 mm - 25,4 mm

Precision:



Performance:

